

NITRILE GLOVE ASSEMBLY TECHNICAL PRODUCT DATASHEET REV-04-2020

# NITRILE GLOVE ASSEMBLY

The Nitrile glove assembly combine Nitrile replacement hand gloves with your chosen type of sleeve.



## NITRILE HAND GLOVE

The assembly comes with two pairs of replacement gloves as standard. Larger quantities of Nitrile gloves can be purchased separately. The following are Nitrile hand glove key features.

- Monufactured from Nitrile
- · Good chemical resistance.
- Flock lined for user comfort.
- · Textured fingertips.
- Supplied as handed only, not ambidextrous.

## NITRILE HAND GLOVE CERTIFICATION AND STANDARDS

- Complies with European Directive PPE Category 3
- Protection against mechanical risks. EN388:2003
- Protection against chemicals. EN ISO 374-1
- Protection against micro-organisms. EN ISO 374-5:2016



**AJKLOT** 

See overleaf for details on standards.

4101X

3001

# NITRILE HAND GLOVE SPECIFICATIONS

Colour	Green	
Hand Sizes (See Details Overleaf)	7 - 8 - 9 - 10	
Thickness	0.4mm - 0.015"	
Length	320mm - 13"	
Recommended in-use lifespan	< 3 Months (Light duty)	
Recommended Temperature Range	-30°C to + 110°C (-22F to 230F)	

# NITRILE HAND GLOVE ADDITIONAL INFORMATION

Shelf Life	1 Year		
Storage	Dry conditions. temperature between +5°C to +25°C (41°F to 77°F) Avoid direct sunlight or ozone sources.		
Disposal	Non Recyclable. Classified as non-toxic waste (assuming cleaned when disposed).		
Constituents / Allergies	Does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.		

# HAND GLOVE FEATURES & TECHNOLOGY







Great Dexterity



Great Comfort

# CONNECTOR CUFF & O RINGS

The assembly comes with a connector cuff and four O-rings as a standard. Both of these glove accessories can be purchased separately.



# SLEEVE TYPES AVAILABLE

Sleeves are available in Butadyl. Hypalon (CSM), Nitrile, Butyl, Neoprene or EDPM and all of them come in two different port sizes, 8" – 203mm and 10"-254mm. For more details, click on each individual sleeve to access their specific technical information.







#### BUTADYL SLEEVE

- · Good chemical resistance
- FDA Compliant
- Antistatic
- UV Resistant





### HYPALON CSM SLEEVE

- · Good chemical resistance
- UV resistant
- Excellent impermeability against gases





#### NITRILE SLEEVE

- · Good chemical resistance
- Sterile
- Antistatic





#### **BUTYL SLEEVE**

- · Good chemical resistance
- Anti-static
- UV Resistant
- · Excellent impermeability against gases





## NEOPRENE SLEEVE

- Good Chemical resistance
- · Good mechanical protection
- UV resistant





#### EDPM SLEEVE

- Good chemical resistance
- FDA compliant
- Antistatic
- UV Resistant



## CERTIFICATION LEGENDS







Acetone Acetonitrile Dichloromethone Carbon Disulphide Toluene Diethylomine Tetrahydrofuran Ethyl acetate n-Héptane Sodium Hydroxide (40%) Sulphuric Acid (96%) Nitrid Acid (65%) Acetic Acid (99%) Ammonia (NH4OH) (25%) Hydrogen Peroxide (30%) Hýdrofluoric acid (20%) Formladehyde (37%)

Methanol






TYPE A: Gloves have achieved level 2 or areater against six of the chemicals listed in EN ISO 374-1 (below). The tested chemicals are identified by their code letters under the flask oictoorom.

TYPE B: Achieved level 2 or greater against at least three of the chemicals

TYPE C: Achieved at least a level 1 against one of the chemicals.





\*For dulling during cut resistance test (6.2), the coupe test results are only indicative while the TDM cut resistance test (6.3) is the reference performance result.

## FN 420 SIZING SYSTEM

SIZE	HAND Ø (MM)	LENGTH (MM)	MIN. LENGTH OF GLOVE				
6	152	160	220				
7	178	171	230				
8	203	182	240				
9	229	182	250				
10	254	204	260				

